



260w Mono Solar Panel 1640 X 992 X 35MM 3.2mm Monocrystalline Pv Panel

Basic Information

Place of Origin: China
Brand Name: Linksun
Certification: CE
Model Number: LS-260M
Minimum Order Quantity: 100PCS
Packaging Details: 1pcs/carton
Delivery Time: 5-8days

• Payment Terms: 30% TT in advance, 70% balance before

delivery.

Supply Ability: 1000pieces per week



Product Specification

Product Name: 260w Mono Solar Panels

• Solar Cell: Monocrystalline Silicon Solar Cell

Application: Homes Camping
Contract Dimension: 1640*992*35
Back Sheet: White
Protection Class: IP 65

• Front Material: 3.2mm High Transmission Tempered Glass

Output Cables: 4 Mm² Length: 900 Mm
 Highlight: 260w Mono Solar Panel,

Mono Solar Panel 1640 x 992 x 35MM, 3.2mm monocrystalline pv panels

260w Mono Solar Panel 1640 X 992 X 35MM 3.2mm Monocrystalline Pv Panels

This 260W monocrystalline solar panel, measuring 1640 x 992 x 35mm with a 3.2mm thickness, is perfect for residential and commercial use. Engineered for high efficiency, it provides reliable energy output with a compact design. The robust construction ensures durability and long-term performance, making it an excellent choice for sustainable energy solutions. Ideal for those looking to reduce energy costs and environmental impact, this panel offers a cost-effective and eco-friendly way to harness solar power.

Product Features:

1) High photoelectric conversion efficiency:

The photoelectric conversion efficiency of monocrystalline silicon solar cells is about 15%, with the highest reaching 24%, which is currently the highest photoelectric conversion efficiency among all types of solar cells.

2)Low production cost:

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

3)Long service life:

The service life of monocrystalline silicon solar cells is relatively long, generally reaching around 20 years, with the highest reaching 25 years.

4)Good low light performance:

Monocrystalline silicon solar cells can also perform well under low light conditions, making them suitable for use in solar lamps, solar lawn lamps, etc.

Product Details:

Model	LS-260M
Maximum Power(Pmax)	260W
Maximum Power Voltage(Vmp)	29.6V
Maximum Power Current(Imp)	8.72A
Open Circuit Voltage(Voc)	35.6V
Short Circuit Current(Isc)	9.59A
Power Tolerance(Positive)	3%
Cell Type	Mono-crystalline
Contract Dimensions(mm)	1640*992*35mm
Weight(KGS)	21kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.28%
Cell number	60(6x10)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm ² ,Length:900mm



FAQ:

Q1: What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2: Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3: Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4: Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao, Ningbo. Welcome your visit if you like.

Q5: Where are your goods exported? A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China