



## 290 Watt 30V Polycrystalline Silicon Pv Panels 35.95V Crystalline Solar Modules

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE
- Model Number: LS-290P
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.



### Product Specification

- Durability: High
- Efficiency: High
- Installation: Easy
- Lifespan: Long
- Material: Polycrystalline
- Power: 290w
- Size: 1640\*992\*35mm
- Warranty: 25 Years
- Highlight: **30V polycrystalline silicon pv panels,  
290 watt polycrystalline silicon pv panels,  
35.95V crystalline solar modules**

for more products please visit us on [monosolarpanel.com](http://monosolarpanel.com)

## 290 Watt 30V Polycrystalline Silicon Pv Panels 35.95V Crystalline Solar Modules

These 290W polycrystalline silicon PV panels, operating at 30V with a maximum voltage of 35.95V, are designed for high efficiency and reliability. Ideal for residential and commercial installations, they offer robust energy output and durable performance. The crystalline solar modules maximize energy production while ensuring long-term sustainability. Perfect for reducing energy costs and environmental impact, these panels provide a cost-effective and eco-friendly solution for harnessing solar power.

### Product Features:

#### 1)Durable&Sturdy

The product contains anodized aluminum alloy frame. It can work in the temperature between -40 ~85 and withstand the high winds (2400Pa) and snow loads (5400Pa).

#### 2)Wide application

Common applications includes RV, camper, car, marine, residential rooftop, remote farm, traffic signs, etc.

#### 3)eco-friendly

It uses polycrystalline solar cells. A poly crystalline solar panel is economical, eco-friendly, consumes less energy, and can function in all temperatures.

### Product Details:

Model	LS-290P
Maximum Power(Pmax)	290W
Maximum Power Voltage(Vmp)	30V
Maximum Power Current(Imp)	9.66A
Open Circuit Voltage(Voc)	35.95V
Short Circuit Current(Isc)	10.63A
Power Tolerance(Positive)	3%
Cell Type	Poly-crystalline
Contract Dimensions(mm)	1640*992*35mm
Weight(KGS)	21kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	17.35%
Cell number	60(6x10)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm <sup>2</sup> ,Length:900mm



---

**FAQ:**

Q1:What's the solar panels warranty?

A: 5 year's warranty.If you have any questions about our quality during use,you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



**Ningbo Linksun Energy Science & Technology Co., LTD**



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China