

# 280w Black Solar PV Panels Black Polycrystalline Pv Solar Panel

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100PCS
- Packaging Details:
- Delivery Time:
- Payment Terms:

• Supply Ability:

1pcs/carton 5-8days 30% TT in advance, 70% balance before delivery. 1000pieces per week



Color:	Black
Connector:	MC4
Efficiency:	16.86%
• Lifespan:	25 Years
Material:	Polycrystalline
Operating Temperature:	-40 To +85
• Power:	280W
Product Name:	280W Black Solar PV Panel
• Size:	1640*992*35mm
Warranty:	25 Years
• Weight:	21kg
• Highlight:	280w Black Solar PV Panels, 29.85V Black Solar PV Panels, 280 watt polycrystalline pv solar panel

China

CE

Linksun

LS-280P

# Linksun 280w Black Polycrystalline solar panels

The 280W Black Solar PV Panels with Black Polycrystalline modules deliver high efficiency and modern aesthetics. These panels ensure excellent performance in various light conditions, making them suitable for residential and commercial applications. The sleek all-black design enhances visual appeal, blending seamlessly with contemporary architecture. Durable and low-maintenance, these panels provide reliable long-term energy production. Ideal for eco-conscious individuals, they help reduce electricity costs and carbon footprint, supporting sustainable and renewable energy solutions.

### **Product Features:**

### 1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

### 2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

#### 3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

#### **Product Details:**

Model	LS-280P
Maximum Power(Pmax)	280W
Maximum Power Voltage(Vmp)	29.85V
Maximum Power Current(Imp)	9.38A
Open Circuit Voltage(Voc)	35.88V
Short Circuit Current(Isc)	10.31A
Power Tolerance(Positive)	3%
Cell Type	Poly-crystalline
Contract Dimensions(mm)	1640*992*35mm
Weight(KGS)	21kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.86%
Cell number	60(6x10)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm <sup>2</sup> ,Length:900mm



#### FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders? A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order? A:Yes,of course.The lead time for samples is 7-10 days.		
Q4:Are you manufacturer or a trading company? A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.		
Q5:Where are your goods exported? A:We can export to all over the world.		
	LINKS	
	• +8615888168085 Sales02@zjlinksun.com · · · · · · · · · · · · · · · · ·	

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China