



250w Black Solar PV Panels Polycrystalline Pv Solar Panel

Our Product Introduction

for more products please visit us on monosolarpanel.com

Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE
- Model Number: LS-250M
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.
- Supply Ability: 1000pieces per week



Product Specification

- Color: Black
- Connector: MC4
- Efficiency: 15.62%
- Lifespan: 25 Years
- Material: Monocrystalline
- Name: 250W Black Solar PV Panel
- Power: 250W
- Size: 1640*992*35mm
- Temperature Range: -40 ~+85
- Warranty: 25 Years
- Weight: 21kg
- Highlight: 250w Black Solar PV Panels,
29.5V Black Solar PV Panels,
250 watt polycrystalline pv solar panel



Product Description

Linksun all black 250w monocrystalline solar panels

These 250W black solar PV panels are polycrystalline, designed for residential applications. They provide efficient energy conversion with a stylish, uniform appearance that complements any roof. Built to endure extreme weather, they ensure long-term reliability and performance. Installation is straightforward with pre-drilled holes and compatibility with various mounting systems. Ideal for homeowners looking for an affordable and effective renewable energy solution.

Product Features

1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

Product Details:

Model	LS-250M
Maximum Power(Pmax)	250W
Maximum Power Voltage(Vmp)	29.5V
Maximum Power Current(Imp)	8.47A
Open Circuit Voltage(Voc)	35.2V
Short Circuit Current(Isc)	9.36A
Power Tolerance(Positive)	3%
Cell Type	Mono-crystalline
Contract Dimensions(mm)	1640*992*35mm
Weight(KGS)	21kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	15.62%
Cell number	60(6x10)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm ² ,Length:900mm



FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty.If you have any questions about our quality during use,you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China