



260w All Black Solar Panels Mono Crystalline Panel

Basic Information

Place of Origin: China
Brand Name: Linksun
Certification: CE
Model Number: LS-260M
Minimum Order Quantity: 100PCS
Packaging Details: 1pcs/carton
Delivery Time: 5-8days

• Payment Terms: 30% TT in advance, 70% balance before

delivery.

Supply Ability: 1000pieces per week



Product Specification

Connector Type: MC4Efficiency: 16.28%

Material: Monocrystalline

Max System Voltage: 1000VPower: 260W

• Product Name: 260W Black Solar PV Panel

• Size: 1640*992*35mm

Temperature Range: -40 ~+85Warranty: 25 YearsWeight: 21kg

• Highlight: 260w all black solar panels,

all black solar panels 1000V, 2620 watt mono crystalline panel

Linksun all black 260w monocrystalline solar panels

The 260W All Black Monocrystalline Solar Panels deliver high efficiency and sleek aesthetics for residential and commercial use. These panels offer excellent performance in various light conditions, ensuring reliable energy production. The all-black design enhances the visual appeal, blending seamlessly with modern architecture. With robust construction, they guarantee long-term durability and low maintenance. Ideal for ecoconscious users, these panels provide a sustainable solution to reduce electricity costs and carbon footprint while supporting renewable energy goals.

Product Features

1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

Product Details:

Model	LS-260M
Maximum Power(Pmax)	260W
Maximum Power Voltage(Vmp)	29.6V
Maximum Power Current(Imp)	8.72A
Open Circuit Voltage(Voc)	35.6V
Short Circuit Current(Isc)	9.59A
Power Tolerance(Positive)	3%
Cell Type	Mono-crystalline
Contract Dimensions(mm)	1640*992*35mm
Weight(KGS)	21kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.28%
Cell number	60(6x10)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm ² ,Length:900mm



FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao, Ningbo. Welcome your visit if you like.

Q5:Where are your goods exported?

LIINKSUN

Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



e monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China