

## 270w Black Solar PV Panels Monocrystalline House Solar **Panels**

### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100PCS

China

CE

Linksun

LS-270M

5-8days

- Packaging Details: 1pcs/carton
- Delivery Time:
- Payment Terms:
- Supply Ability:
- 30% TT in advance, 70% balance before delivery. 1000pieces per week

## **Product Specification**

• Material:

• Efficiency:

• Warranty:

• Weight:

• Highlight:

• Origin:

• Size:

- Monocrystalline Product Name: 270W Black Solar PV Panel MC4 • Connector Type: 16.66% China 1640\*992\*35mm -40°C - 85°C • Temperature Range: 25 Years 21 Kg
  - 270w Black Solar PV Panels, 21kg Black Solar PV Panels, 270 watt house solar panels



# Linksun all black 270w monocrystalline solar panels

These high-efficiency 270W black solar PV panels are monocrystalline, ideal for residential use. They offer superior performance with a sleek, modern design that blends seamlessly with your roof. Engineered for durability, they withstand harsh weather conditions while maximizing energy output. Easy to install, these panels come with pre-drilled holes and are compatible with various mounting systems, ensuring a hasslefree setup. Perfect for homeowners seeking reliable, sustainable energy solutions.

### **Product Features**

#### 1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

#### 2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

#### 3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

### **Product Details:**

Model	LS-270M
Maximum Power(Pmax)	270W
Maximum Power Voltage(Vmp)	29.8V
Maximum Power Current(Imp)	9.02A
Open Circuit Voltage(Voc)	35.8V
Short Circuit Current(Isc)	9.92A
Power Tolerance(Positive)	3%
Cell Type	Mono-crystalline
Contract Dimensions(mm)	1640*992*35mm
Weight(KGS)	21kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.66%
Cell number	60(6x10)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm <sup>2</sup> ,Length:900mm



#### FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders? A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order? A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company? A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported? A:We can export to all over the world.

Links	Ningbo Linksun Energy Science & Technology Co., LTD
-	8168085 Sales02@zjlinksun.com