




Linksun All Black Solar Panels 280w Monocrystalline Solar Panels

Our Product Introduction

for more products please visit us on monosolarpanel.com

Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE
- Model Number: LS-280M
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.
- Supply Ability: 1000pieces per week



Product Specification

- Connector Type: MC4
- Efficiency: 16.86%
- Material: Mono-crystalline
- Max Power: 280W
- Number Of Cells: 60(6x10)
- Product Name: 280W Black Solar PV Panel
- Size: 1640*992*35mm
- Warranty: 25 Years
- Highlight: **280W black solar panels,
black solar panels 280w,
280 watt monocrystalline solar panels**

Product Description

Linksun all black 280w monocrystalline solar panels

The 280W All Black Monocrystalline Solar Panels combine high efficiency with a sleek, modern look. Designed for both residential and commercial applications, these panels perform exceptionally well in various light conditions. The all-black design enhances aesthetic appeal, seamlessly integrating with contemporary architecture. Built to last, they offer durability and low maintenance, ensuring reliable long-term energy production. Ideal for those seeking to lower electricity bills and reduce their carbon footprint, these panels provide a sustainable and efficient energy solution.

Product Features

1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

Product Details:

Model	LS-280M
Maximum Power(Pmax)	280W
Maximum Power Voltage(Vmp)	29.85V
Maximum Power Current(Imp)	9.38A
Open Circuit Voltage(Voc)	35.88V
Short Circuit Current(Isc)	10.31A
Power Tolerance(Positive)	3%
Cell Type	Mono-crystalline
Contract Dimensions(mm)	1640*992*35mm
Weight(KGS)	21kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.86%
Cell number	60(6x10)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm ² ,Length:900mm

FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty.If you have any questions about our quality during use,you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China