

All Black 290w Black Solar PV Panels Monocrystalline Lightweight Solar Panels

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100PCS
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- 1pcs/carton 5-8days 30% TT in advance, 70% balance before delivery. 1000pieces per week



Product Specification

Efficiency:	17.25%
 Lifespan: 	25 Years
Material:	Monocrystalline
Power:	290W
 Product Name: Size:	290W Black Solar PV Panel 1640*992*35mm
 Size.Temperature Range:	-40 ~+85
• Warranty:	25 Years
Weight:	21kg
 Highlight: 	290w Black Solar PV Panels, 21kg Black Solar PV Panels, 290 watt Monocrystalline lightweight so nanels

panels

China

CE

Linksun

LS-290M



Linksun all black 290w monocrystalline solar panels

The All Black 290W Monocrystalline Lightweight Solar Panels combine high efficiency with a sleek, modern design. These panels are perfect for residential and commercial use, offering excellent performance even in low-light conditions. The lightweight construction ensures easy installation, while the all-black aesthetic enhances visual appeal. Durable and low-maintenance, they provide reliable, long-term energy production. Ideal for reducing electricity costs and carbon footprint, these panels support sustainable energy solutions with their superior efficiency and stylish appearance.

Product Features

1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

Product Details:

Model	LS-290M
Maximum Power(Pmax)	290W
Maximum Power Voltage(Vmp)	30V
Maximum Power Current(Imp)	9.66A
Open Circuit Voltage(Voc)	35.95V
Short Circuit Current(Isc)	10.63A
Power Tolerance(Positive)	3%
Cell Type	Mono-crystalline
Contract Dimensions(mm)	1640*992*35mm
Weight(KGS)	21kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	17.25%
Cell number	60(6x10)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm ² ,Length:900mm



FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders? A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order? A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company? A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

Ningbo Linksun Energy Science & Technology Co., LTD +8615888168085 Sales02@zjlinksun.com monosolarpanel.com Ind., Floor, No. 1 Building, Wanyang Entrepreneurial City, Yuyao, Zhejiang Province, China		