

Linksun 310w Pure Black Solar Panels Polycrystalline Pv Module

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 10
- Packaging Details: 1
- Delivery Time:
- Payment Terms:
- Supply Ability:
- LS-310P 100PCS 1pcs/carton 5-8days 30% TT in advance, 70% balance before delivery. 1000pieces per week



Product Specification

Connector Type:	MC4
Efficiency:	16.28%
IP Rating:	IP65
Material:	Poly-crystalline
• Maximum System Voltage:	1000V
Operating Temperature:	-40°C To +85°C
Product Name:	310W Black Solar PV Panel
• Size:	1950*992*40mm
Temperature Range:	-40°C To +85°C
Warranty:	25 Years
• Weight:	23kg
• Highlight:	310w pure black solar panels, pure black solar panels 1000V, 310 watt polycrystalline pv module

China

CE

Linksun

Linksun 310w Black Polycrystalline solar panels

The 310W Pure Black Solar Panels with Polycrystalline PV modules deliver high efficiency and a sleek, modern look. Ideal for residential and commercial use, they perform reliably in various light conditions. The pure black design enhances the visual appeal, seamlessly integrating with contemporary architecture. Durable and low-maintenance, these panels ensure long-term energy production. Perfect for eco-conscious users, they help reduce electricity costs and carbon footprint, offering a sustainable and efficient energy solution for diverse applications.

Product Features:

1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

Product Details:

Model	LS-310P
Maximum Power(Pmax)	310W
Maximum Power Voltage(Vmp)	36.5V
Maximum Power Current(Imp)	8.49A
Open Circuit Voltage(Voc)	45.65V
Short Circuit Current(Isc)	9.34A
Power Tolerance(Positive)	3%
Cell Type	Poly-crystalline
Contract Dimensions(mm)	1950*992*40mm
Weight(KGS)	23kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.28%
Cell number	72(6x12)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm ² ,Length:900mm



LINKS Ningbo Linksun Energy Science & Technology Co., LTD		
& +861588	sales02@zjlinksun.com	@ monosolarpanel.com
2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China		