



395 Watt 108 Cells Solarpanel Bifacial Monocrystalline Solar Cell

Basic Information

Place of Origin: China
Brand Name: Linksun
Certification: CE
Model Number: LS-395M
Minimum Order Quantity: 100PCS
Packaging Details: 1pcs/carton
Delivery Time: 5-8days

• Payment Terms: 30% TT in advance, 70% balance before

delivery.

Supply Ability: 1000pieces per week



Product Specification

• Cell Type: Mono-crystalline PERC,182x91mm

• Certifications: CE,BSCI

• Dimensions: 1722*1134*30mm(67.79x44.64x1.18 Inches)

• Efficiency: 20.20%

• Frame: Black, Anodized Aluminum Alloy

• IP Rating: IP68 Rated

• Number Of Cells: 108(6x18)(Half-Cell)

• Operating Temperature: -40 To 85°C

• Product Name: 395W Bifacial Solar Panels

Warranty: 25 YearsWeight: 25.5kg

• Highlight: 395 watt solarpanel bifacial,

108 Cells solarpanel bifacial, 395W monocrystalline solar cell

395 Watt 108 Cells Solarpanel Bifacial Monocrystalline Solar Cell

The 395 Watt 108 Cell Bifacial Monocrystalline Solar Panel is designed for high efficiency and durability. With bifacial technology, it captures sunlight from both sides, enhancing energy production. The 108 monocrystalline cells ensure superior performance in various conditions. Ideal for residential and commercial use, it offers reliable and sustainable energy. The robust design ensures long-lasting performance, even in harsh environments. This solar panel is a smart choice for those seeking to maximize their solar energy yield and reduce electricity costs.

Product Features:

1)Higher efficiency

With the ability of capturing sunlight from both sides, our product of bifacial solar panel can provide up to 21,96% more efficient compared with the common solar panel.

2)Easy to install and use

The pre-drilled holes on the back of the panel make it quick to mount on the roof or other situation.

3)Advanced Technology

As one of the most efficient solar technologies in the industry, HJT technology can make products less affected by changes in temperature. Bifacial products pass more sunlight up to 95%.

Product Details:

Model	LS-395M		
Maximum Power(Pmax)	395W		
Maximum Power Voltage(Vmp)	30.62V		
Maximum Power Current(Imp)	12.90A		
Open Circuit Voltage(Voc)	36.73V		
Short Circuit Current(Isc)	13.69A		
Power Tolerance(Positive)	3%		
Cell Type	Mono-crystalline PERC,182x91mm		
Product Dimension(mm)	1722*1134*30mm(67.79x44.64x1.18 inches)		
Weight(KGS)	25.5kg		
Protection Class	IP68 rated		
Maximum System Voltage	DC 1500V		
Operating Temperature Range	-40 ~85		
Module Efficiency STC	20.20%		
Cell number	108(6x18)(Half-Cell)		
	(F)2.0mm ultra clear embossed semi-		
Front Glass	tempered coated glass		
	(B)2.0mm semi-tempered glass		
Frame Type	Black, Anodized Aluminum Alloy		
Connector Type	MC4		
Output Cables	4.0 mm ² (0.006 inches ²),Length:1100mm		
Output Gables	4.0 mm (0.000 mones),Length. 1100mm		

Temperature Characteristics		Packing Configuration	
Temp.Coeff.of Isc(TK Isc)	0.048%/	Container	40'HQ
Temp.Coeff.of Voc(TK Voc)	-0.27%/	Pieces per pallet	72
Temp.Coeff.of Pmax(TK Pmax)	-0.34%/	Pallets per container	13
Normal operating cell Temperature	44±2	Pieces per container	936



FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao, Ningbo. Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China