



400 Watt 1500V Bifacial Solar Panels Monocrystalline Solar Panel For Charging

Our Product Introduction

for more products please visit us on monosolarpanel.com

Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE
- Model Number: LS-400M
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.
- Supply Ability: 1000pieces per week



Product Specification

- Cell Type: Mono-crystalline PERC, 182x91mm
- Certifications: CE, BSCI
- Connector Type: MC4
- Dimensions: 1722*1134*30mm (67.79x44.64x1.18 Inches)
- Frame Type: Black, Anodized Aluminum Alloy
- Junction Box: IP68 Rated
- Max System Voltage: DC 1500V
- Panel Efficiency: 20.46%
- Product Name: 400W Bifacial Solar Panels
- Temperature Range: -40°C To +85°C
- Tolerance: 0-+3%
- Warranty: 25 Years
- Weight: 25.5kg
- Highlight: 400 watt Bifacial Solar Panels, 1500V Bifacial Solar Panels, 400W Monocrystalline Bifacial Solar Panels

Product Description

400 Watt 1500V Bifacial Solar Panels Monocrystalline Solar Panel For Charging

The 400 Watt Bifacial Solar Panels are designed for high efficiency and reliability, operating at 1500V with advanced monocrystalline technology. These panels capture sunlight from both sides, significantly increasing energy output. Perfect for charging applications, they are ideal for residential, commercial, and industrial use. The robust construction ensures durability and long-lasting performance. With their ability to utilize reflected light, these panels maximize power generation, offering a smart solution for reducing electricity costs and promoting sustainable energy. Their sleek design and superior efficiency make them an excellent investment.

Product Features:

1)Higher efficiency

With the ability of capturing sunlight from both sides,our product of bifacial solar panel can provide up to 21,96% more efficient compared with the common solar panel.

2)Easy to install and use

The pre-drilled holes on the back of the panel make it quick to mount on the roof or other situation.

3)Advanced Technology

As one of the most efficient solar technologies in the industry,HJT technology can make products less affected by changes in temperature. Bifacial products pass more sunlight up to 95%.

Product Details:

| | |
|-----------------------------|--|
| Model | LS-400M |
| Maximum Power(Pmax) | 400W |
| Maximum Power Voltage(Vmp) | 30.83V |
| Maximum Power Current(Imp) | 12.98A |
| Open Circuit Voltage(Voc) | 36.93V |
| Short Circuit Current(Isc) | 13.76A |
| Power Tolerance(Positive) | 3% |
| Cell Type | Mono-crystalline PERC,182x91mm |
| Product Dimension(mm) | 1722*1134*30mm(67.79x44.64x1.18 inches) |
| Weight(KGS) | 25.5kg |
| Protection Class | IP68 rated |
| Maximum System Voltage | DC 1500V |
| Operating Temperature Range | -40 ~85 |
| Module Efficiency STC | 20.46% |
| Cell number | 108(6x18)(Half-Cell) |
| Front Glass | (F)2.0mm ultra clear embossed semi-tempered coated glass (B)2.0mm semi-tempered glass |
| Frame Type | Black,Anodized Aluminum Alloy |
| Connector Type | MC4 |
| Output Cables | 4.0 mm ² (0.006 inches ²),Length:1100mm |

| Temperature Characteristics | | Packing Configuration | |
|-----------------------------------|---------|-----------------------|-------|
| Temp.Coeff.of Isc(TK Isc) | 0.048%/ | Container | 40'HQ |
| Temp.Coeff.of Voc(TK Voc) | -0.27%/ | Pieces per pallet | 72 |
| Temp.Coeff.of Pmax(TK Pmax) | -0.34%/ | Pallets per container | 13 |
| Normal operating cell Temperature | 44±2 | Pieces per container | 936 |



FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty.If you have any questions about our quality during use,you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China