



410w IP68 Solar Panel Bifacial N Type Bifacial Solar Panel Frameless

Basic Information

Place of Origin: ChinaBrand Name: LinksunCertification: CE

Model Number: LS-D410M
Minimum Order Quantity: 100PCS
Packaging Details: 1pcs/carton
Delivery Time: 5-8days

• Payment Terms: 30% TT in advance, 70% balance before

delivery.

• Supply Ability: 1000pieces per week



Product Specification

Connector: MC4Efficiency: 21.00%

Material: Mono-crystalline
Operating Temperature: -40°C To +85°C

• Power: 410W

• Product Name: 410W Frameless Solar Panel

• Size: 1722*1134*5.5mm(67.80x44.65x0.22

Inches)

• Type: N Type Mono-crystalline ,182x91mm

Warranty: 25 YearsWaterproof Level: IP68 RatedWeight: 23kg

Highlight: 410w solar panel bifacial,

IP68 solar panel bifacial frameless, 410 watt n type bifacial solar panel

Linksun Mono Bi-facial 410w Double glass,frameless M10 TOPCON for large public buildings

The 410W IP68 Bifacial N-Type Frameless Solar Panel is designed for high efficiency and durability. Its bifacial technology captures sunlight from both sides, boosting energy output. The frameless design and IP68 rating ensure robust performance and resistance to water and dust, making it ideal for challenging environments. With N-type cells, this panel offers superior efficiency and longevity, perfect for commercial and industrial installations. It provides reliable and sustainable energy solutions for large-scale solar projects

Product Features:

1)High aesthetics

The overall frameless design of the double glass frameless photovoltaic module is more aesthetically pleasing and can be integrated into the exterior of the building.

2)Good weather resistance and reliability

Adopting a double glass design can effectively improve the weather resistance and reliability of the component, and extend its service life.

3)More convenient installation

Due to the borderless design, installation is more convenient and fast, reducing installation costs and labor hours.

4)Higher power generation efficiency

By adopting more advanced production processes and materials, the photoelectric conversion efficiency is improved, resulting in higher power generation compared to traditional components.

Product Details:

Model	LS-D410M	
Maximum Power(Pmax)	410W	
Maximum Power Voltage(Vmp)	31.25V	
Maximum Power Current(Imp)	13.12A	
Open Circuit Voltage(Voc)	37.94V	
Short Circuit Current(Isc)	13.85A	
Power Tolerance(Positive)	3%	
Cell Type	N type Mono-crystalline ,182x91mm	
Product Dimension(mm)	1722*1134*5.5mm(67.80x44.65x0.22 inches)	
Weight(KGS)	23kg	
Protection Class	IP68 rated	
Maximum System Voltage	DC 1500V	
Operating Temperature Range	-40 ~85	
Module Efficiency STC	21.00%	
Cell number	108(6x18)(Half-Cell)	
	(F)2.0mm ultra clear embossed double layer	
Front Glass	colorless glass	
	(B)2.0mm black mesh glazed tempered glass	
Connector Type	MC4	
Output Cables	4.0 mm²(0.006 inches²),Length:1100mm	

Temperature Characteristics		Packing Configuration	
Temp.Coeff.of Isc(TK Isc)	0.046%/	Container	40'GP
Temp.Coeff.of Voc(TK Voc)	-0.25%/	Pieces per pallet	72
Temp.Coeff.of Pmax(TK Pmax)	-0.30%/	Pallets per container	13
Normal operating cell Temperature	45±2	Pieces per container	936



Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao, Ningbo. Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China