



600W 34.4V Silicon Solar Panels 1500V Mono Pv Module

Basic Information

Place of Origin: ChinaBrand Name: LinksunCertification: CE

Model Number: LS-D600M
Minimum Order Quantity: 100PCS
Packaging Details: 1pcs/carton
Delivery Time: 5-8days

• Payment Terms: 30% TT in advance, 70% balance before

delivery.

• Supply Ability: 1000pieces per week



Product Specification

• Connector: MC4

Frame: Silver, Anodized Aluminum Alloy
Product Name: 600W Silicon Solar Panels

Protection Level: IP68Service Life: 25 Years

• Type: Mono-crystalline PERC,210x105mm

Warranty: 25 YearsEfficiency: 21.2%

• Size: 2172*1303*35mm(85.51*51.29*1.38inches)

• Maximum System Voltage: 1500V DC-(H)

• Highlight: 600w Silicon Solar Panels,

34.4V Silicon Solar Panels, 1500V mono pv module

Linksun M12/120H Monocrystalline 600w solar panels with 25 Years Warranty

These high-performance monocrystalline solar panels deliver 600W of power and come with a 25-year warranty, ensuring long-term reliability and efficiency. Designed for optimal energy conversion, they are ideal for residential and commercial installations. With advanced technology and robust construction, these panels maximize energy output even in low-light conditions, providing a sustainable and cost-effective energy solution.

Product Features:

1)High Efficiency

High modules conversion efficiency. Grade A solar cell and IP68 Rated waterproof solar panel connectors. This solar panel has 5 year 95% output warranty, 10 year 90% output warranty, 25 year 80% output warranty.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades. The IP68 rated junction box and solar connectors can withstand dirt, dust, debris, and water splashes.

3)High Tolerance

It can tolerate any part of the battery's shading, and performs well in low light conditions due to an increase in the number of batteries receiving more sunlight.

Product Details:

Model	LS-D600M	
Maximum Power(Pmax)	600W	
Maximum Power Voltage(Vmp)	34.4V	
Maximum Power Current(Imp)	17.44A	
Open Circuit Voltage(Voc)	41.5V	
Short Circuit Current(Isc)	18.52A	
Power Tolerance(Positive)	3%	
Cell Type	Mono-crystalline PERC,210x105mm	
Product Dimension(mm)	2172*1303*35mm(85.51*51.29*1.38inches)	
Weight(KGS)	30.9kg	
Protection Class	IP68	
Maximum System Voltage	1500V DC-(H)	
Operating Temperature Range	-40 ~85	
Module Efficiency STC	21.2%	
Cell number	120(6x20)(Half-Cell)	
Front Glass	3.2mm High Transmission Tempered	
	Glass(0.13inches)	
Connector Type	MC4	
Output Cables	4 mm ² ,Length:1300mm	

Temperature Characteristics		Packing Configuration	
Temp.Coeff.of Isc(TK Isc)	0.05%/	Container	40'HQ
Temp.Coeff.of Voc(TK Voc)	-0.27%/	Pieces per pallet	31
Temp.Coeff.of Pmax(TK Pmax)	-0.34%/	Pallets per container	18
Normal operating cell Temperature	44±2	Pieces per container	558

FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao, Ningbo. Welcome your visit if you like.

Q5:Where are your goods exported? A:We can export to all over the world.

LIINKSUN

Ningbo Linksun Energy Science & Technology Co., LTD

+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China