



675w 39.0V Silicon Solar Panels Mobile Solar Panels IP68

Our Product Introduction

for more products please visit us on monosolarpanel.com

Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE
- Model Number: LS-D675M
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.
- Supply Ability: 1000pieces per week



Product Specification

- Cell Type: N Type Mono-crystalline 210x105mm
- Efficiency: 21.7%
- Warranty: 25 Years
- Protection Class: IP68 Rated
- Power: 675W
- Product Name: 675W Silicon Solar Panels
- Weight: 34kg
- Size: 2384*1303*33mm(93.85x51.29x1.30 Inches)
- Frame Type: Silver, Anodized Aluminum Alloy
- Highlight: **675w Silicon Solar Panels,
39.0V Silicon Solar Panels,
675 watt mobile solar panels IP68**

Linksun Monocrystalline 675w silicon solar panels with 25 Years Warranty

These top-tier monocrystalline silicon solar panels offer 675W of power and include a 25-year warranty for guaranteed performance and durability. Perfect for residential and commercial applications, they are engineered for superior energy efficiency and reliability. The advanced design ensures maximum energy capture, even in low-light conditions, making them a sustainable and cost-effective energy solution.

Product Features:

1)High Efficiency

High modules conversion efficiency. Grade A solar cell and IP68 Rated waterproof solar panel connectors. This solar panel has 5 year 95% output warranty, 10 year 90% output warranty, 25 year 80% output warranty.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades. The IP68 rated junction box and solar connectors can withstand dirt, dust, debris, and water splashes.

3)High Tolerance

It can tolerate any part of the battery's shading, and performs well in low light conditions due to an increase in the number of batteries receiving more sunlight.

Product Details:

| | |
|-----------------------------|--|
| Model | LS-D675M |
| Maximum Power(Pmax) | 675W |
| Maximum Power Voltage(Vmp) | 39.0V |
| Maximum Power Current(Imp) | 17.31A |
| Open Circuit Voltage(Voc) | 46.9V |
| Short Circuit Current(Isc) | 18.24A |
| Power Tolerance(Positive) | 3% |
| Cell Type | N type Mono-crystalline 210x105mm |
| Product Dimension(mm) | 2384*1303*33mm(93.85x51.29x1.30 inches) |
| Weight(KGS) | 34kg |
| Protection Class | IP68 rated |
| Maximum System Voltage | DC 1500V |
| Operating Temperature Range | -40 ~85 |
| Module Efficiency STC | 21.7% |
| Cell number | 132(6x22)(Half-Cell) |
| Front Glass | 3.2mm High Transmission Tempered Glass(0.13 inches) |
| Connector Type | MC4 |
| Output Cables | 4.0 mm ² (0.006 inches ²),Length:1300mm |

| Temperature Characteristics | | Packing Configuration | |
|-----------------------------------|---------|-----------------------|-------|
| Temp.Coeff.of Isc(TK Isc) | 0.05%/ | Container | 40'HQ |
| Temp.Coeff.of Voc(TK Voc) | -0.25%/ | Pieces per pallet | 66 |
| Temp.Coeff.of Pmax(TK Pmax) | -0.29%/ | Pallets per container | 9 |
| Normal operating cell Temperature | 41±3 | Pieces per container | 594 |

FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty.If you have any questions about our quality during use,you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China