



575W Linksun Monocrystalline Silicon Solar Panels With 25 Years Warranty

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE、BSCI
- Model Number: LS-575M
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.
- Supply Ability: 1000pieces per week



Product Specification

- Highlight: Outdoor Mono Crystalline Solar Panels,
575w Silicon Solar Panels,
Waterproof Silicon Solar Panels

for more products please visit us on monosolarpanel.com

Product Description

Linksun Monocrystalline 575w Silicon Solar Panels With 25 Years Warranty

Introducing the 575W Linksun Monocrystalline Silicon Solar Panels, engineered for superior efficiency and longevity. These panels utilize advanced monocrystalline silicon technology, ensuring high performance even in low-light environments. With an IP68 waterproof rating, they are built to withstand harsh weather conditions, guaranteeing reliable operation. Supported by a 25-year warranty, you can trust in their durability and consistent energy production. Ideal for residential, commercial, and industrial use, Linksun solar panels are your perfect choice for sustainable and efficient energy solutions.

Product Features:

1)High Efficiency

High modules conversion efficiency. Grade A solar cell and IP68 Rated waterproof solar panel connectors. This solar panel has 5 year 95% output warranty, 10 year 90% output warranty, 25 year 80% output warranty.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades. The IP68 rated junction box and solar connectors can withstand dirt, dust, debris, and water splashes.

3)High Tolerance

It can tolerate any part of the battery's shading, and performs well in low light conditions due to an increase in the number of batteries receiving more sunlight.

Product Details:

Model	LS-575M
Maximum Power(Pmax)	575W
Maximum Power Voltage(Vmp)	42.41V
Maximum Power Current(Imp)	13.56A
Open Circuit Voltage(Voc)	51.28V
Short Circuit Current(Isc)	14.27A
Power Tolerance(Positive)	3%
Cell Type	N type Mono-crystalline,182x91mm
Product Dimension(mm)	2279*1134*5.5mm(89.72*44.64*0.22inches)
Weight(KGS)	31.5kg
Protection Class	IP68
Maximum System Voltage	1500V DC-(H)
Temperature Range	-40 ~85
Module Efficiency STC	22.25%
Cell number	144(6x24)(Half-Cell)
Front Glass	(F)2.0mm ultra clear embossed double layer colorless glass (B)2.0mm semi-tempered glass
Connector Type	MC4
Output Cables	4 mm ² ,Length:1300mm

Temperature Characteristics		Packing Configuration	
Temp.Coeff.of Isc(TK Isc)	0.046%/	Container	40'GP
Temp.Coeff.of Voc(TK Voc)	-0.25%/	Pieces per pallet	72
Temp.Coeff.of Pmax(TK Pmax)	-0.30%/	Pallets per container	10
Normal operating cell Temperature	45±2	Pieces per container	720

**FAQ:**

Q1:What's the solar panels warranty?

A: 5 year's warranty.If you have any questions about our quality during use,you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China